



180-072 (06)  
Fiber Optic Test Adapter, Plug  
MIL-DTL-38999 Series I



**MIL-DTL-38999 test adapter (plug)**

**How To Order**



06 - PLUG ADAPTER  
FOR USE WITH RECEPTACLE CONNECTOR

U.S. PATENT NO. 5,960,137

**Material and Finish**

- Barrel: See Table II
- Insert, Coupling Nut: Hi-Grade Engineering Thermoplastic
- Alignment Sleeve: Zirconia Ceramic
- Misc. Hardware: Stainless Steel
- Retaining Clips: BeCu Alloy
- Lock Cap, Lock Nut: Al Alloy/Anodize

**Notes**

For fiber optic test probe jumper, see Glenair drawing ABC54705



**180-072 (06)**  
**Fiber Optic Test Adapter, Plug**  
**MIL-DTL-38999 Series I**

**Table I: Shell Size and Insert Arrangements**

Shell Size & Insert Arrangement	Shell Size Code Ref.	Ø A Max
11-2	B	.964 (24.5)
13-4	C	1.141 (29.0)
15-5	D	1.266 (32.2)
15-97	D	1.266 (32.2)
17-8	E	1.391 (35.3)
19-11	F	1.500 (38.8)
21-16	G	1.625 (41.3)
23-21	H	1.750 (44.5)
23-99	H	1.750 (44.5)
25-20	J	1.875 (47.6)
25-29	J	1.875 (47.6)
25-37A	J	1.875 (47.6)
25-37B	J	1.875 (47.6)

**Table II: Material and Finish**

Code	Material	Finish
M	Aluminum Alloy	Electroless Nickel
NF		Cadmium/Olive Drab

